

PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





## EU Type Examination Certificate

Date: 2020/11/11

## n. 469204604/OE

Validity: 2025/11/10

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: (Responsible of the PPE)	SDE MOTORSPORT s.r.l. via Giorgione, 5 – 31030 ALTIVOLE (TV) – ITALIA		
Type of PPE:	motorcyclists' protective footwear		
Category of PPE:	II : "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.		
Model	"RAVE Dry FORU30W" col. BROWN (24)		
Description:	fastening system: by means of laces; processing: Ago; outsole: black rubber "GATTUSO G05944" (MF0246N); upper: "Testa di moro" brown leather "PELLE BOV. DAKAR 16/18 IDRO T.M." (PE0144X); vamp and quarter lining: grey knitting marked "FORMA" in black color, grey foam material, white membrane and white knitting coupled to each other "FOD.TEPOR + ATL.ROVESCIATA + ST.F." (FO0207); collar lining: brown leather "FOD. VIT. IDRO. CARIBU' 08/10" (PE0200);		
The second secon	insole: light-blue semirigid polymeric material coupled with black foam material and covered with the vamp and quarter lining in contact with the removable insock "STP ART RAVE DIMA G2202151" (MF0390); <u>removable insock (perforated)</u> : white foam material coupled with grey non-woven fabric in contact with the user "FSB ECON.PE150 + TNT" (MF0360); <u>gearshift lever protective insert</u> : "Testa di moro" brown leather "PELLE BOV. DAKAR 16/18 IDRO T.M." (PE0144X).		
	The boots also have the following inserts in polymeric material stitched onto the upper, as follows: - <u>internal and external ankle insert</u> : black disk coupled with black foam material.		
Technical Standard:	EN 13634:2017 Protective footwear for motorcycle riders – Requirements and test methods		
Intended use:	use by motorcyclists for normal road activities, mainly on urban roads (e.g. scooter, etc.)		
Size range:	from 36 to 48		
Technical File:	DC-12653		
Test report:	RCT n°3913703		
	Stanismo 10		



PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





## EU Type Examination Certificate

Date: 2020/11/11	n. <b>469204604/OE</b>	Validity: 2025/11/10
Functions and performance levels:	Requirements according to EN 13634:2017: all mandatory of Height of upperHeight of upperlevel 1Impact abrasion resistance of the upperlevel 2Impact cut resistance of the upperlevel 2Transverse rigidity of the whole footwearlevel 2	2
	Optional requirements according to EN 13634:2017: WR = water resistance of the whole footwear.	
	NOTE: the Technical Standard provides 2 performance levels of performance.	with level 2 meaning the higher
	<ul> <li>CE Marking;</li> <li>name/Trademark of the Manufacturer;</li> <li>item designation (= commercial name + alphanumeric c</li> <li>pictogram to indicate the motorcycle use + nr./year levels of performance reached during laboratory tests + c</li> <li>date of production (month and year) + pictogram instruct</li> <li>size indication;</li> <li>additional information: "Designed in", "Made in" + box</li> </ul>	of the referen <mark>ce Stan</mark> dard + optional requirement WR; cting to read the User Manual;
	and in Italy in Romania 3	
EN13634 Level 1 - 2 - RAVE Dry F	2 - 2 WR	
LOT#XXXX		TRO .

NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).

